

proSeries

Process air simplified.

- 1 Budget Friendly
- 2 Eliminates Emissions
- 3 Tailored for Smaller Retrofit Applications
- 4 Simple Design for Easy Maintenance
- 5 Small Footprint



Product Specifications

proAir-5000

Product Specifications			
Standard Model Number	PA-2R-XX		
Instrument Air Specifications			
Max. Dry Air Flow Rate	Standard: 5 scfm	Air Dryer Type	Heatless Regenerative Desiccant
Max. Air Pressure	125 PSIG	Flow Meter Accuracy	±0.5% of Full Scale (Optional)
Air Compressor Power	2 HP per compressor	Air Filtration	Pre and Post Dryer Filters
Air Compressor Type	Rocking Piston		
Wet Air Receiver	30 Gal. Vertical Tank	Dew Point	-40°C (-40°F) PDP
Wet Air Receiver Tank Drain	Electric Auto-Drain		
Electrical Specifications			
Max. System Power Usage	5,000 W	Power Input	120/240 VAC Split
Enclosure Specifications			
Weight	800 LBS	Walls/Insulation	R6 Insulated Panelling
Dimensions	60"x 28"x 66"	Flooring	Standard Steel Plate
Access/Egress	Reach-in/Unmanned	Ventilation	Exhaust Fan and Gravity Backdraft Damper
Design Temperature	-40°C (-40°F) to +40°C (+104°F)		
Heater	2,000 W Forced Air Heater	Exhaust Fan	120 VAC, 1/12 HP
Lighting	LED Lights		